

WHAT IS CLAIMED IS:

1.           A storage unit comprising:
  - a channel control portion for receiving a data input/output request;
  - a cache memory for storing data;
  - a disk control portion for performing input/output processing on data in accordance with said data input/output request; and
  - a plurality of disk drives for storing data, wherein at least two of said disk drives input data to and output it from said disk control portion at different communication speeds.
2.           The storage unit according to claim 1, wherein:
  - said storage unit has a plurality of communication paths for connecting at least one of said disk drives in such a manner as to constitute a loop defined by the fiber channel standards; and
  - each of said communication speeds is different for each of said communication paths.
3.           A storage unit comprising:
  - a disk drive for storing data;
  - a disk control portion for communicating with said disk drive to thereby input said data to and output it from said disk drive;
  - a generation portion for generating a clock signal by using a pulse signal transferred for said communication;

an identification portion for identifying a frequency of said pulse signal;

a frequency division portion for dividing a frequency of said clock signal at a frequency division ratio that corresponds to a frequency of said pulse signal; and

a synchronization portion for synchronizing said pulse signal with said clock signal having said divided frequency.

4. The storage unit according to claim 3, wherein said communication is performed through a communication path which is provided to connect said disk control portion and at least one of said disk drives in such a manner as to constitute a loop defined by the FC-AL fiber channel standards.

5. The storage unit according to claim 3, wherein said identification portion comprises:

a charge accumulation portion for outputting a voltage that corresponds to a quantity of charge accumulated therein;

a charge quantity variation portion for varying said quantity of said charge accumulated in said charge accumulation portion, at a certain variation rate;

a charge quantity variation suppression portion for inhibiting said variation only during a certain lapse of time each time a signal level of said pulse signal is switched;

a signal output portion for outputting a signal that corresponds to whether said voltage output from said charge accumulation portion satisfies a criterion;

a time measurement portion for measuring a lapse of time that has elapsed since said quantity of said charge accumulated in said charge accumulation portion started to vary; and

a frequency identification portion for identifying said frequency based on said lapse of time from a moment when said quantity of said charge started to vary to a moment when said signal that indicates that said voltage of said charge accumulation portion satisfies said criterion was output.

6. The storage unit according to claim 5, wherein said communication is performed through a communication path provided to connect said disk control portion and at least one of said disk drives in such a manner as to constitute a loop defined by the FC-AL fiber channel standards.

7. The storage unit according to claim 5, wherein:

said charge quantity variation portion comprises a charging portion for charging said charge accumulation portion; and

said charge quantity variation suppression portion comprises:

a pulse deviation signal generation portion

for generating a pulse deviation signal having its phase as shifted with respect to that of said pulse signal by certain time; and

a discharging portion for discharging said charge accumulation portion only in a period when there is a potential difference between said pulse signal and said pulse deviation signal.

8. A storage unit comprising:

a disk drive for storing data;

a disk control portion for communicating with said disk drive to thereby input said data to and output it from said disk drive;

a generation portion for generating a clock signal by using a pulse signal transferred for said communication;

a communication specifications decision portion for deciding whether said pulse signal satisfies said communication specifications, when said pulse signal is read in a period of said clock signal;

a frequency division portion for dividing a frequency of said clock signal in accordance with a result of said decision; and

a synchronization portion for synchronizing said pulse signal with said clock signal having said divided frequency.

9. The storage unit according to claim 8, wherein said communication is performed through a communication path which is provided to connect said

disk control portion and at least one of said disk drives in such a manner as to constitute a loop defined by the FC-AL fiber channel standards.

10. A circuit for shaping a communication signal, comprising:

- a generation portion for generating a clock signal by using a pulse signal transferred for communication;

- an identification portion for identifying a frequency of said pulse signal;

- a frequency division circuit for dividing a frequency of said clock signal at a frequency division ratio that corresponds to a frequency of said pulse signal; and

- a synchronization portion for synchronizing said pulse signal with said clock signal having said divided frequency.

11. The circuit according to claim 10, wherein said identification portion comprises:

- a charge accumulation portion for outputting a voltage that corresponds to a quantity of charge accumulated therein;

- a charge quantity variation portion for varying said quantity of said charge accumulated in said charge accumulation portion, at a certain variation rate;

- a charge quantity variation suppression portion for inhibiting said variation only during a

certain lapse of time each time a signal level of said pulse signal is switched;

a signal output portion for outputting a signal that corresponds to whether said voltage output from said charge accumulation portion satisfies a criterion;

a time measurement portion for measuring a lapse of time that has elapsed since said quantity of said charge accumulated in said charge accumulation portion started to vary; and

a frequency identification portion for identifying said frequency based on said lapse of time from a moment when said quantity of said charge started to vary to a moment when said signal that indicates that said voltage of said charge accumulation portion satisfies said criterion was output.

12. The circuit according to claim 11, wherein:

said charge quantity variation portion comprises a charging portion for charging said charge accumulation portion; and

said charge quantity variation suppression portion comprises:

a pulse deviation signal generation portion for generating a pulse deviation signal having its phase as shifted with respect to that of said pulse signal by certain time; and

a discharging portion for discharging said charge accumulation portion only in a period when there

is a potential difference between said pulse signal and said pulse deviation signal.

13. A circuit for shaping a communication signal, comprising:

a generation portion for generating a clock signal by using a pulse signal transferred for communication;

a communication specifications decision portion for deciding whether said pulse signal satisfies specifications of said communication, when said pulse signal is read in a period of said clock signal;

a frequency division portion for dividing a frequency of said clocks signal in accordance with a result of said decision; and

a synchronization portion for synchronizing said pulse signal with said clock signal having said divided frequency.